

Cylindrical Type Proximity Sensor

■ Features

- Improved the noise immunity with dedicated IC
- Built-in reverse polarity protection circuit (DC 3-wire type)
- Built-in surge protection circuit
- Built-in over-current protection circuit (DC type)
- Long life cycle and high reliability, and simple operation
- IP67 protection structure (IEC standard)
- Replaceable for micro switches and limit switches

⚠ Please read "Safety Considerations" in operation manual before using.



■ Specifications

● DC 2-wire type

※When the □ model name is X, it is non-polarity model.

| Model | PRT08-1.5DO PRT08-1.5DC PRT08-1.5DO-V | PRT08-2DO PRT08-2DC | PRT12-2□DO PRT12-2□DC | PRT12-4□DO PRT12-4□DC | PRT18-5□DO PRT18-5□DC | PRT18-8□DO PRT18-8□DC | PRT30-10□DO PRT30-10□DC PRT30-10DO-V | PRT30-15□DO PRT30-15□DC |
|----------------------------------|--|-------------------------------------|---|--------------------------|-----------------------------|--------------------------|--|----------------------------|
| Sensing distance | 1.5mm | 2mm | 2mm | 4mm | 5mm | 8mm | 10mm | 15mm |
| Hysteresis | Max. 10% of sensing distance | | | | | | | |
| Standard sensing target | 8×8×1mm (iron) | | 12×12×1mm (iron) | | 18×18×1mm (iron) | 25×25×1mm (iron) | 30×30×1mm (iron) | 45×45×1mm (iron) |
| Setting distance | 0 to 1.05mm | 0 to 1.4mm | 0 to 1.4mm | 0 to 2.8mm | 0 to 3.5mm | 0 to 5.6mm | 0 to 7mm | 0 to 10.5mm |
| Power supply (operating voltage) | 12-24VDC $\overline{=}$ (10-30VDC $\overline{=}$) | | | | | | | |
| Leakage current | Max. 0.6mA | | | | | | | |
| Response frequency $\times 1$ | 1.5kHz | 1kHz | 1.5kHz | 500Hz | 350Hz | 400Hz | 200Hz | |
| Residual voltage $\times 2$ | Max. 3.5V (non-polarity type is Max. 5V) | | | | | | | |
| Affection by Temp. | Max. $\pm 10\%$ for sensing distance at ambient temperature 20°C (for PRT08 Series: $\pm 20\%$ Max.) | | | | | | | |
| Control output | 2 to 100mA | | | | | | | |
| Insulation resistance | Over 50M Ω (at 500VDC megger) | | | | | | | |
| Dielectric strength | 1,500VAC 50/60Hz for 1 minute | | | | | | | |
| Vibration | 1mm amplitude at frequency of 10 to 55Hz (for 1 min) in each X, Y, Z direction for 2 hours | | | | | | | |
| Shock | 500m/s 2 (approx. 50G) in X, Y, Z direction for 3 times | | | | | | | |
| Indicator | Operation indicator: Red LED | | | | | | | |
| Environment | Ambient temperature | -25 to 70°C, storage: -30 to 80°C | | | | | | |
| | Ambient humidity | 35 to 95% RH, storage: 35 to 95% RH | | | | | | |
| Protection circuit | Surge protection circuit | | Surge protection circuit, Over-current protection circuit | | | | | |
| Protection structure | IP67 (IEC standard) | | | | | | | |
| Cable | Ø3.5mm, 3-wire, 2m (AWG24, Core diameter: 0.08mm, Number of cores: 40, Insulator diameter: Ø1mm) | | Ø4mm, 2-wire, 2m | | Ø5mm, 2-wire, 2m | | | |
| | (AWG22, Core diameter: 0.08mm, Number of cores: 60, Insulator diameter: Ø1.25mm) | | | | | | | |
| Material | Case/Nut: Nickel plated brass, Washer: Nickel plated iron, Sensing surface: Polybutylene terephthalate, Standard cable (black): Polyvinyl chloride (PVC), Oil resistant cable (gray): Oil resistant polyvinyl chloride (PVC) | | | | | | | |
| Approval | CE | | | | | | | |
| Weight $\times 3$ | Approx. 64g (approx. 52g) | | Approx. 84g (approx. 72g) | | Approx. 122g (approx. 110g) | | Approx. 207g (approx. 170g) | |

※1: The response frequency is the average value. The standard sensing target is used and the width is set as 2 times of the standard sensing target, 1/2 of the sensing distance for the distance.

※2: Before using non-polarity type, check the condition of connected device because residual voltage is 5V.

※3: The weight includes packaging. The weight in parentheses is for unit only.

※The '□' of model name is for power type. 'D' is 12-24VDC, 'X' is non-polarity 12-24VDC.

※Environment resistance is rated at no freezing or condensation.

(A) Photoelectric Sensors

(B) Fiber Optic Sensors

(C) Door/Area Sensors

(D) Proximity Sensors

(E) Pressure Sensors

(F) Rotary Encoders

(G) Connectors/ Connector Cables/ Sensor Distribution Boxes/Sockets

(H) Temperature Controllers

(I) SSRs / Power Controllers

(J) Counters

(K) Timers

(L) Panel Meters

(M) Tacho / Speed / Pulse Meters

(N) Display Units

(O) Sensor Controllers

(P) Switching Mode Power Supplies

(Q) Stepper Motors & Drivers & Controllers

(R) Graphic/ Logic Panels

(S) Field Network Devices

(T) Software

PR Series

■ Specifications

● DC 3-wire type

| | | | | | | | | |
|----------------------------------|--|--|--|--|--|--|--|--|
| Model | PR08-1.5DN PR08-1.5DP PR08-1.5DN2 PR08-1.5DP2 PRL08-1.5DN PRL08-1.5DP PRL08-1.5DN2 PRL08-1.5DP2 | PR08-2DN PR08-2DP PR08-2DN2 PR08-2DP2 PRL08-2DN PRL08-2DP PRL08-2DN2 PRL08-2DP2 | PR12-2DN PR12-2DP PR12-2DN2 PR12-2DP2 PRS12-2DN PRS12-2DP PRS12-2DN2 PRS12-2DP2 | PR12-4DN PR12-4DP PR12-4DN2 PR12-4DP2 PRS12-4DN PRS12-4DP PRS12-4DN2 PRS12-4DP2 PRL12-4DN PRL12-4DP PRL12-4DN2 PRL12-4DP2 | PR18-5DN PR18-5DP PR18-5DN2 PR18-5DP2 PR18-5DN-V PRL18-5DN PRL18-5DP PRL18-5DN2 PRL18-5DP2 | PR18-8DN PR18-8DP PR18-8DN2 PR18-8DP2 PRL18-8DN PRL18-8DP PRL18-8DN2 PRL18-8DP2 | PR30-10DN PR30-10DP PR30-10DN2 PR30-10DP2 PRL30-10DN PRL30-10DP PRL30-10DN2 PRL30-10DP2 | PR30-15DN PR30-15DP PR30-15DN2 PR30-15DP2 PRL30-15DN PRL30-15DP PRL30-15DN2 PRL30-15DP2 |
| Sensing distance | 1.5mm | 2mm | 2mm | 4mm | 5mm | 8mm | 10mm | 15mm |
| Hysteresis | Max. 10% of sensing distance | | | | | | | |
| Standard sensing target | 8×8×1mm (iron) | | 12×12×1mm (iron) | | 18×18×1mm (iron) | 25×25×1mm (iron) | 30×30×1mm (iron) | 45×45×1mm (iron) |
| Setting distance | 0 to 1.05mm | 0 to 1.4mm | 0 to 1.4mm | 0 to 2.8mm | 0 to 3.5mm | 0 to 5.6mm | 0 to 7mm | 0 to 10.5mm |
| Power supply (operation voltage) | 12-24VDC= (10-30VDC=) | | | | | | | |
| Current consumption | Max. 10mA | | | | | | | |
| Response frequency ^{※1} | 1.5kHz | 1kHz | 1.5kHz | 500Hz | | 350Hz | 400Hz | 200Hz |
| Residual voltage | Max. 2.0V | | Max. 1.5V | | | | | |
| Affection by Temp. | Max. ±10% for sensing distance at ambient temperature 20°C, PR08 Series: Max. ±20% | | | | | | | |
| Control output | Max. 200mA | | | | | | | |
| Insulation resistance | Over 50MΩ (at 500VDC megger) | | | | | | | |
| Dielectric strength | 1,500VAC 50/60Hz for 1 minute | | | | | | | |
| Vibration | 1mm amplitude at frequency of 10 to 55Hz (for 1 min) in each X, Y, Z direction for 2 hours | | | | | | | |
| Shock | 500m/s ² (approx. 50G) in X, Y, Z direction for 3 times | | | | | | | |
| Indicator | Operation indicator: Red LED | | | | | | | |
| Environment | Ambient temperature | -25 to 70°C, storage: -30 to 80°C | | | | | | |
| | Ambient humidity | 35 to 95%RH, storage: 35 to 95%RH | | | | | | |
| Protection circuit | Surge protection circuit, Reverse polarity protection circuit, Over-current protection circuit | | | | | | | |
| Protection structure | IP67 (IEC standard) | | | | | | | |
| Material | Case/Nut: Nickel plated brass, Washer: Nickel plated iron, Sensing surface: Polybutylene terephthalate, Standard cable (black): Polyvinyl chloride (PVC), Oil resistant cable (gray): Oil resistant polyvinyl chloride (PVC) | | | | | | | |
| Cable | Ø3.5mm, 3-wire, 2m (AWG24, Core diameter: 0.08mm, Number of cores: 40, Insulator diameter: Ø1mm) | | Ø4mm, 3-wire, 2m | | Ø5mm, 3-wire, 2m | | | |
| | (AWG22, Core diameter: 0.08mm, Number of cores: 60, Insulator diameter: Ø1.25mm) | | | | | | | |
| Approval | CE | | | | | | | |
| Weight ^{※2} | PR: Approx. 64g (approx. 52g) PRL: Approx. 66g (approx. 54g) | | PR: Approx. 84g (approx. 72g) PRS: Approx. 82g (approx. 70g) PRL: Approx. 88g (approx. 76g) | | PR: Approx. 122g (approx. 110g) PRL: Approx. 142g (approx. 130g) | | PR: Approx. 207g (approx. 170g) PRL: Approx. 247g (approx. 210g) | |


※1: The response frequency is the average value. The standard sensing target is used and the width is set as 2 times of the standard sensing target, 1/2 of the sensing distance for the distance.

※2: The weight includes packaging. The weight in parentheses in for unit only.

※Environment resistance is rated at no freezing or condensation.

■ Specifications

● AC 2-wire type

| Model | PR12-2AO PR12-2AC | PR12-4AO PR12-4AC | PR18-5AO PR18-5AC PRL18-5AO PRL18-5AC | PR18-8AO PR18-8AC PRL18-8AO PRL18-8AC | PR30-10AO PR30-10AC PRL30-10AO PRL30-10AC | PR30-15AO PR30-15AC PRL30-15AO PRL30-15AC |
|----------------------------------|--|-----------------------------------|---|--|---|--|
| Sensing distance | 2mm | 4mm | 5mm | 8mm | 10mm | 15mm |
| Hysteresis | Max. 10% of sensing distance | | | | | |
| Standard sensing target | 12×12×1mm (iron) | | 18×18×1mm (iron) | 25×25×1mm (iron) | 30×30×1mm (iron) | 45×45×1mm (iron) |
| Setting distance | 0 to 1.4mm | 0 to 2.8mm | 0 to 3.5mm | 0 to 5.6mm | 0 to 7mm | 0 to 10.5mm |
| Power supply (operation voltage) | 100-240VAC~ (85-264VAC~) | | | | | |
| Leakage current | Max. 2.5mA | | | | | |
| Response frequency※1 | 20Hz | | | | | |
| Residual voltage | Max. 10V | | | | | |
| Affection by Temp. | Max. ±10% for sensing distance at ambient temperature 20°C | | | | | |
| Control output | 5 to 150mA | | 5 to 200mA | | | |
| Insulation resistance | Over 50MΩ (at 500VDC megger) | | | | | |
| Dielectric strength | 2,500VAC 50/60Hz for 1 minute | | | | | |
| Vibration | 1mm amplitude at frequency of 10 to 55Hz (for 1 min) in each X, Y, Z direction for 2 hours | | | | | |
| Shock | 500m/s ² (approx. 50G) in X, Y, Z direction for 3 times | | | | | |
| Indicator | Operation indicator: Red LED | | | | | |
| Environment | Ambient temperature | -25 to 70°C, storage: -30 to 80°C | | | | |
| | Ambient humidity | 35 to 95%RH, storage: 35 to 95%RH | | | | |
| Protection circuit | Surge protection circuit | | | | | |
| Protection structure | IP67 (IEC standard) | | | | | |
| Cable | Ø4mm, 2-wire, 2m | | Ø5mm, 2-wire, 2m | | | |
| | (AWG22, Core diameter: 0.08mm, Number of cores: 60, Insulator diameter: Ø1.25mm) | | | | | |
| Insulation type | Double insulation or reinforced insulation (Mark:  , dielectric strength between the measuring input part and the power part: 1kV) | | | | | |
| Material | Case/Nut: Nickel plated brass, Washer: Nickel plated iron, Sensing surface: Polybutylene terephthalate, Standard cable (black): Polyvinyl chloride (PVC) | | | | | |
| Approval | CE | | | | | |
| Weight※2 | Approx. 84g (approx. 66g) | | PR: Approx. 130g (approx. 118g) PRL: Approx. 142g (approx. 130g) | | PR: Approx. 207g (approx. 170g) PRL: Approx. 245g (approx. 208g) | |

※1: The response frequency is the average value. The standard sensing target is used and the width is set as 2 times of the standard sensing target, 1/2 of the sensing distance for the distance.

※2: The weight includes packaging. The weight in parentheses in for unit only.

※Environment resistance is rated at no freezing or condensation.

(A)
Photoelectric
Sensors

(B)
Fiber
Optic
Sensors

(C)
Door/Area
Sensors

(D)
Proximity
Sensors

(E)
Pressure
Sensors

(F)
Rotary
Encoders

(G)
Connectors/
Connector Cables/
Sensor Distribution
Boxes/Sockets

(H)
Temperature
Controllers

(I)
SSRs / Power
Controllers

(J)
Counters

(K)
Timers

(L)
Panel
Meters

(M)
Tacho /
Speed / Pulse
Meters

(N)
Display
Units

(O)
Sensor
Controllers

(P)
Switching
Mode Power
Supplies

(Q)
Stepper Motors
& Drivers
& Controllers

(R)
Graphic/
Logic
Panels

(S)
Field
Network
Devices


(T)
Software

PR Series


■ Dimensions

(unit: mm)


● PR(T)08-1.5D □




● PR(T)08-2D □




● PR(T)18-5D □




● PR(T)18-8D □




● PRS12-2D □




● PRS12-4D □




● PR(T)30-10D □




● PR(T)30-15D □




● PR(T)12-2D □




● PR(T)12-4D □



● PRL08-1.5D □



● PRL08-2D □




Cylindrical Type


■ Dimensions

(unit: mm)


● PRL12-2D □




● PR12-2A □




● PRL12-4D □



● PR12-4A □




● PRL18-5D □




● PRL18-5A □

● PR18-5A □




● PRL18-8D □




● PRL18-8A □

● PR18-8A □




● PRL30-10D □




● PRL30-10A □

● PR30-10A □




● PRL30-15D □



● PRL30-15A □

● PR30-15A □



(A) Photoelectric Sensors

(B) Fiber Optic Sensors

(C) Door/Area Sensors

(D) Proximity Sensors

(E) Pressure Sensors

(F) Rotary Encoders

(G) Connectors/ Connector Cables/ Sensor Distribution Boxes/Sockets

(H) Temperature Controllers

(I) SSRs / Power Controllers

(J) Counters

(K) Timers

(L) Panel Meters

(M) Tacho / Speed / Pulse Meters

(N) Display Units

(O) Sensor Controllers

(P) Switching Mode Power Supplies

(Q) Stepper Motors & Drivers & Controllers

(R) Graphic/ Logic Panels


(S) Field Network Devices

(T) Software

PR Series


■ Control Output Diagram and Load Operation

◎ DC 2-wire type





■ Connections

◎ DC 2-wire type




※The load can be connected to either wire.


◎ DC 3-wire type




◎ AC 2-wire type



◎ DC 3-wire type




◎ AC 2-wire type




※The load can be connected to either wire.

Cylindrical Type


■ Sensing Distance Feature Data by Target Material and Size




● PRT08-1.5D □




● PRT08-2D □




● PRT12-2D □, PR12-2A □




● PRT12-4D □, PR12-4A □




● PRT18-5D □, PR(L)18-5A □




● PRT18-8D □, PR(L)18-8A □



● PRT30-10D □, PR(L)30-10A □



● PRT30-15D □, PR(L)30-15A □



(A) Photoelectric Sensors

(B) Fiber Optic Sensors

(C) Door/Area Sensors

(D) Proximity Sensors

(E) Pressure Sensors

(F) Rotary Encoders

(G) Connectors/ Connector Cables/ Sensor Distribution Boxes/Sockets

(H) Temperature Controllers

(I) SSRs / Power Controllers

(J) Counters

(K) Timers

(L) Panel Meters

(M) Tacho / Speed / Pulse Meters

(N) Display Units

(O) Sensor Controllers

(P) Switching Mode Power Supplies

(Q) Stepper Motors & Drivers & Controllers


(R) Graphic/ Logic Panels

(S) Field Network Devices


(T) Software

PR Series


■ Sensing Distance Feature Data by Target Material and Size




● PR(L)08-1.5D □




● PR(L)08-2D □




● PR(S/L)12-2D □




● PR(S/L)12-4D □




● PR(L)18-5D □




● PR(L)18-8D □



● PR(L)30-10D □




● PR(L)30-15D □



Cylindrical Type

■ Sensing Distance Feature Data by Parallel (Left/Right) Movement



(A) Photoelectric Sensors

(B) Fiber Optic Sensors

(C) Door/Area Sensors

(D) Proximity Sensors

(E) Pressure Sensors

(F) Rotary Encoders

(G) Connectors/
Connector Cables/
Sensor Distribution
Boxes/Sockets

(H) Temperature Controllers

(I) SSRs / Power Controllers

(J) Counters

(K) Timers

(L) Panel Meters

(M) Tacho /
Speed / Pulse
Meters

(N) Display Units

(O) Sensor Controllers

(P) Switching
Mode Power
Supplies


(Q) Stepper Motors
& Drivers
& Controllers

(R) Graphic/
Logic
Panels

(S) Field
Network
Devices


(T) Software

● PRT08-1.5D□/2D□




| | |
|-------|-------------|
| — | PRT08-1.5D□ |
| - - - | PRT08-2D□ |

● PRT12-2D□/4D□ , PR12-2A□/4A□




| | |
|-------|------------------------|
| — | PRT12-2D□, PR12-2A□ |
| - - - | PRT12-4D□, PR12-4A□ |

● PRT18-5D□/8D□ , PR(L)18-5A□/8A□




| | |
|-------|---------------------------|
| — | PRT18-5D□, PR(L)18-5A□ |
| - - - | PRT18-8D□, PR(L)18-8A□ |

● PRT30-10D□/15D□ , PR(L)30-10A□/15A□




| | |
|-------|-----------------------------|
| — | PRT30-10D□, PR(L)30-10A□ |
| - - - | PRT30-15D□, PR(L)30-15A□ |

● PR(L)08-1.5D□/2D□




| | |
|-------|---------------|
| — | PR(L)08-1.5D□ |
| - - - | PR(L)08-2D□ |

● PR(S/L)12-2D□/4D□




| | |
|-------|---------------|
| — | PR(S/L)12-2D□ |
| - - - | PR(S/L)12-4D□ |

● PR(L)18-5D□/8D□



| | |
|-------|-------------|
| — | PR(L)18-5D□ |
| - - - | PR(L)18-8D□ |

● PR(L)30-10D□/15D□




| | |
|-------|--------------|
| — | PR(L)30-10D□ |
| - - - | PR(L)30-15D□ |

PR Series

■ Proper Usage


◎ Load connections



When using DC or AC 2-wire type proximity sensor, the load must be connected, otherwise internal components may be damaged. The load can be connected to either wire.

◎ In case of the load current is small

● AC 2-wire type



It may cause return failure of load by residual voltage. If the load current is under 5mA, please make sure the residual voltage is less than the return voltage of the load by connecting a bleeder resistor in parallel with the load as shown in the diagram.


$$R \leq \frac{V_s}{I} \text{ (k}\Omega\text{)} \quad P > \frac{V_s^2}{R} \text{ (W)}$$

[I: Action current of load, R: Bleeder resistance, P: Permissible power]

Please make the current on proximity sensor smaller than the return current of load by connecting a bleeder resistor in parallel.

※ W value of Bleeder resistor should be bigger for proper heat dissipation.

● DC 2-wire type




$$R \leq \frac{V_s}{I_o - I_{\text{off}}} \text{ (k}\Omega\text{)} \quad P > \frac{V_s^2}{R} \text{ (W)}$$


[Vs: Power supply, I_o: Min. action current of proximity sensor, I_{off}: Return current of load, P: Number of Bleeder resistance watt]

◎ Mutual-interference & Influence by surrounding metals

When several proximity sensors are mounted close to one another a malfunction of the may be caused due to mutual interference. Therefore, be sure to keep a minimum distance between the two sensors as below chart indicates.



When sensors are mounted on metallic panel, it is required to protect the sensors from being affected by any metallic object except target. Therefore, be sure to provide a minimum distance as below chart indicates.



(unit: mm)

| Model | PRT08-1.5D□ PR(L)08-1.5D□ | PRT08-2D□ PR(L)08-2D□ | PRT12-2D□ PR(S/L)12-2D□ PR12-2A□ | PRT12-4D□ PR(S/L)12-4D□ PR12-4A□ | PRT18-5D□ PR(L)18-5D□ PR(L)18-5A□ | PRT18-8D□ PR(L)18-8D□ PR(L)18-8A□ | PRT30-10D□ PR(L)30-10D□ PR(L)30-10A□ | PRT30-15D□ PR(L)30-15D□ PR(L)30-15A□ |
|-------|------------------------------|--------------------------|--|--|---|---|--|--|
| A | 9 | 12 | 12 | 24 | 30 | 48 | 60 | 90 |
| B | 16 | 24 | 24 | 36 | 36 | 54 | 60 | 90 |
| ℓ | 0 | 8 | 0 | 11 | 0 | 14 | 0 | 15 |
| Ød | 8 | 24 | 12 | 36 | 18 | 54 | 30 | 90 |
| m | 4.5 | 6 | 6 | 12 | 15 | 24 | 30 | 45 |
| n | 12 | 24 | 18 | 36 | 27 | 54 | 45 | 90 |