


Product

# RRB 0315



RRB-0315 is a crimping tool for Super Seal type connectors with seal, uninsulated open barrel connectors, 0.35 - 1.5 mm<sup>2</sup>/AWG 22-16, B/F-Crimp.

- Standard Rigidus frame length provides optimum low handle force for miniature connectors designed for wires smaller than 16 AWG/1.5 mm<sup>2</sup>
- Unique "snap on" locator design for full visibility of connector and wire insertion
- Parallel action for precision and consistent crimp results
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miscrimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Tool-less die closure adjustment for maintenance and calibration
- Small size makes it easy to use in confined work areas
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability



Die profile



Crimp profile

#### TECHNICAL DATA

**Length:** 190 mm/7.48"

**Width:** 21 mm/0.83"

**Height:** 74 mm/2.91"

**Weight:** 317 gr/0.7 lb

**Wire size:** 0.35-1.5 mm<sup>2</sup> / AWG 22-AWG 16

**Crimp dimensions mm/mm<sup>2</sup>:**

0,35 - 0,5/0,75 - 1,5

**Crimp dimensions inch/AWG:**

AWG 22 - AWG 20/AWG 20 - AWG 16

**Connector:** Connectors with seal, 1.5 system type.

**Description:** For non insulated open barrel super seal connectors.

**Life span, cycles:** 50,000