

## **Product**

## **KRB 0115S**



KRB-0115S is a crimping tool for non insulated open barrel connectors, 2.8 + 4.8 mm, 0.1 - 1.5 mm<sup>2</sup>/.110" + .187", AWG 26-16, B/F-Crimp.

- · High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force requirement over competing crimping tools
- · Versatile and easy to customize for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- · Full cycle crimp mechanism to ensure consistent, reliable crimp
- · Ratchet release mechanism to clear miscrimps and obstructions
- · Precision eccentric adjustment for consistent performance and ability to calibrate
- · Hole in handle allows attachment of safety strap
- · Each tool has a unique serial number for traceability





Die profile

Crimp profile

**TECHNICAL DATA** Length: 204 mm/8.03" Width: 22 mm/0.87" Height: 76 mm/2.99" Weight: 560 gr/1.23 lb

Wire size: 0.1-1.5 mm<sup>2</sup> / AWG 26-

Crimp dimensions mm/mm<sup>2</sup>: 0,1 - 0,5 mm<sup>2</sup>/0,5 - 1 mm<sup>2</sup>/0,5 - 1,5 mm<sup>2</sup>

Crimp dimensions inch/AWG: AWG 26 - 20/AWG 20 - 18/AWG 20 -

Connector: Uninsulated open barrel connectors

Description: For uninsulated open

barrel connectors.

Life span, cycles: 50,000