

Digital Clamp Tester

AC Current ,20A/200A/600A ,40mm ϕ CT

Model 2010 (CE)



FEATURES

- Data-hold and Auto power off function.
- Conform to IEC safety requirements
- Additional AC/DC voltage, resistance, diode test, continuity check.

SPECIFICATIONS

Safety standard	: IEC 61010-1, IEC 61010-2-032 ,Installation Category III600V phase to earth
E.M.C. standard	: EN 61326.
Measuring method	: Dual slope integration mode
Display	: 3.5 digit LCD, max. reading of 1999
Jaw opening capability	: 40mm ϕ
Over range indication	: Blanking of all digits except MSD 1
Low battery indication	: "Battery" mark on LCD
Data hold indication	: "DH" mark on LCD
Sampling	: 2 times/sec.
Withstanding voltage	: AC 5500V 1 minute max. (Between the core of CT and outer case)
Operating temperature	: 0°C to 40°C, 80%RH max. (Without condensation)
Storage temperature	: -10°C to 60°C, 70%RH max. (Without condensation)
Power supply	: 1.5V (AM-4,LR03 or AAA) \times 2
Power consumption	: 3.5mW
Auto power off	: Approx.10 minutes later after power on
Battery life	: Approx.500 hours continuous
Size	: 70(W) \times 223(H) \times 34(D)mm
Weight	: Approx. 425g
Accessories	: Hard carrying case.....1 Instruction manual.....1 Test lead.....1set Batteries.....2

Accuracy (23°C \pm 5°C, 80%RH or less)

Function	Range	Accuracy	Maximum input
AC A (50/60Hz) Manual ranging	20A	\pm 1.2% rdg \pm 10 dgt	AC600A
	200A	\pm 1.2% rdg \pm 10dgt	
	600A	\pm 1.0% rdg \pm 8 dgt	
AC V (50/60Hz) DC V Auto ranging	2V	\pm 0.7% rdg \pm 5 dgt	DC 600V or AC 600V rms
	20V	\pm 1.2% rdg \pm 5 dgt	
	200V	\pm 1.2% rdg \pm 5 dgt	
Resistance(Ω) Auto ranging	200 Ω	\pm 1.2% rdg \pm 5 dgt	Input protection 250V rms (30 second)
	2k Ω	\pm 1.2% rdg \pm 5 dgt	
	20k Ω	\pm 1.2% rdg \pm 5 dgt	
	200k Ω	\pm 1.2% rdg \pm 5 dgt	
	2000k Ω	\pm 1.2% rdg \pm 5 dgt	
	20M Ω	\pm 3.0% rdg \pm 10 dgt	
Continuity check	2k Ω	Beeper <approx.300 Ω	250V rms
Diode test	2V	\pm 10% rdg \pm 3dgt	250V rms